Tenax

Ms Super Grip MS POLYMER ONE-COMPONENT ADHESIVE

Paste adhesive specifically for multi-material assembly. Its quick setting, extra strong long-lasting adhesion and flexibility make it ideal for placing undertops, sinks or tubs.









Technical data:

Appearance: transparent or coloured paste

Indicative consumption:

- For grouting: 20-30MT linear
- ◆ For bonding: 30-40MT2

The stated consumption is merely indicative

Indoor









How to apply it:

- The surfaces to be sealed must be dry and free of dust, oil, rust or other contaminants.
- Delimit the joint with adhesive tape.
- Cut off the upper portion of the cartridge above the thread.
- Cut the spout to the desired diameter and screw it onto the cartridge.
- Extrude the product.
- Perfect the seal within 5 min and remove any excess with a cutter.
- Please read the technical data sheet carefully for proper use.

Performance:

Skin formation time at 23°C/45%r.h:

15-30min

Wide range of colours

no

Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.

Tenax



Thread cutting



Spout insertion



Product extrusion



Multimaterial bonding



Multimaterial bonding



Instant bonding