

Thassos T TRANSPARENT SOLID POLYESTER MASTIC

Strong transparent mastic with low yellowing. Thanks to its ease of application and long working time, it is ideal for laying large surfaces, filling, bonding and repairing.



 $\stackrel{\frown}{\mapsto}$ strong bonding

Technical data:

paste

How to apply it:

in the TDS.

•

۵

Density at 25°C gr/cm³: 1.1

Standard colour: transparent

Appearance: transparent

Use clean tools when mixing.

will be applied is clean and dry.

Avoid prolonged contact with air.

Make sure that the material on which the product

To clean tools soiled with mastics, use non-greasy solvents, e.g. Acetone or Butyl Acetate.Use the necessary PPE. Read the technical and safety data sheet carefully.

Close the containers with their original caps for correct storage.

Approximate consumption:

LOW YELLOWING

- For grouting: 20-30 linear meters
- For bonding: 30-40 mt2

The stated duration is only approximate



Quartz

Tenax

THE ORIGINAL SINCE 1956

Mastice

MASTICE POLIESTERE

POLYESTER MASTIC For repearing, filling and bondin

Performance:

Adhesion strength [Mpa]	marble 7.5
Gel time in mass at 25°C	6-8 min
Workability time at 25°C	1 h 30 min
Extraclear	yes
Stability to sunlight	superb
Wet effect	superb
Spreadability	superb
Adhesion on wet	no

Warnings:

Safety measures:

Before use, please read the instructions in the safety data sheet and the notes on the packaging. Close the container after use. For professional use only.

Remove the desired quantity of product from the container and weigh it. Comply with the ratio between the product and its hardener as indicated

If necessary, add liquid or pigment dyes before mixing with the hardener.

When a surface is treated for the first time, it is advisable to evaluate its effect or adhesion on a sample or hidden corner.

EASY TO APPLY

Natural stone





Opening the jar



Addition of hardener



Mixed product appearance



Spatula product



Post mix verticality

Hardened product appearance