

## Toner

### COLOR ENHANCER SEALER

Sealing colour enhancer treatment. The product is characterised by its high performance in terms of protection and toning, high yield and easy application, for a long-lasting effect. Approved for food contact. Approved for food contact.



**LONG-LASTING PROTECTION AND TONING**

**EASY TO APPLY**

**DOES NOT CREATE FILMS**

#### Technical data:

- ◆ **Density at 25°C gr/cm³:** 900
- ◆ **Standard colour:** colourless
- ◆ **Appearance:** opalescent liquid

#### Indicative duration:

- ◆ **Indoor:**  
12-24 months
- ◆ **Outdoor:**  
6-12 months

The stated duration is merely indicative



Solvent based



For food contact



Indoor  
Outdoor

#### Tools:

- ◆ Brush
- ◆ Cloth
- ◆ Sponge
- ◆ Fleece



Natural stone



Quartz

#### How to apply it:

- ◆ Apply the product to a dry, clean surface.
- ◆ Apply the product evenly.
- ◆ Do not expose to sunlight during application.
- ◆ If applied improperly, a sticky film will form.
- ◆ After a few minutes, wipe off excess product with a clean cloth.
- ◆ Do not step on the treated surface for 4-6 hours.
- ◆ After 24 hours, the treatment will be absorbed by the material, achieving the desired protection.

#### Indicative consumption 1 l:

Consumption depends on the porosity of the material - yield per coat

Lava stone and marble	30-40m <sup>2</sup>
-----------------------	---------------------

Quartz	20-30m <sup>2</sup>
--------	---------------------

#### Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

#### Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.





Opening the can



Dampen the cloth



Product application



Excess removal



Protective effect



Final result